

Standard System includes:

- Fitted Carrying Case
- User Manual



The HI-1501 is Holaday's most popular Microwave Oven Leakage Meter.

The device provides accuracy and portability for widespread use by oven manufacturers, service technicians, regulatory agencies and public health officials.

It is virtually immune to failure caused by excessive fields. Three ranges are available for increased resolution in leakage measurement.

Specifications

Frequency Response
Ranges
Response Time

Maximum Power Density
Power Supply
Dimensions
(3.5" x 6" x 2.5")
Probe Length
Probe Cable Length

Standard Accessories

Fitted Carrying Case
User Manual

2450 MHz
0-2, 0-10, 0-100 mW/cm²
Fast Mode: 1sec
Slow Mode: 2.5 secs (to 90% of Impulse Level)
2 W/cm²
2 ea. 9V Alkaline Batteries
8.9 W x 15.3 H x 6.4 D cm

30cm (12")
1.2m (4')

USA

Tel +1.512.531.6400
Fax +1.512.531.6500

Finland

Tel +358.2.8383.300
Fax +358.2.8651.233

UK

Tel +44.1438.730.700
Fax +44.1438.730.751

France

Tel +33.1.48.65.34.03
Fax +33.1.48.65.43.69

China

Tel +8610.8275.5086
Fax +8610.8275.5537

Japan

Tel +81.3.3813.7100
Fax +81.3.3813.8068